

## Specifications CX30B ZTS

### Engine

Displacement \_\_\_\_\_ 1331 cm<sup>3</sup>  
Power \_\_\_\_\_ 23 hp  
Max torque \_\_\_\_\_ 80,1 Nm  
Emissions level \_\_\_\_\_ Not regulated in EU

### Hydraulic system

Variable displacement pumps type \_\_\_\_\_ axial piston  
Flow delivery \_\_\_\_\_ 2 x 26,4 l/min  
Gear pump delivery \_\_\_\_\_ 14,3 l/min  
Maximum operating pressure \_\_\_\_\_ 230 bar  
Auxiliary Flow \_\_\_\_\_ 40.7 l/min  
Auxiliary Pressure \_\_\_\_\_ 230 bar

### Slewing & travel speed

Slewing speed \_\_\_\_\_ 8,7 / 8,8 rpm  
Boom slewing angle (left/right) \_\_\_\_\_ 60° / 55°  
Travel Speed - Low (1st) \_\_\_\_\_ 2,3 km/h  
Travel Speed - High (2nd) \_\_\_\_\_ 4,1 km/h

## Specifications CX35B

### Engine

Displacement \_\_\_\_\_ 1642 cm<sup>3</sup>  
Power \_\_\_\_\_ 30 hp  
Max torque \_\_\_\_\_ 98,4 Nm  
Emissions level \_\_\_\_\_ Stage IIIA

### Hydraulic system

Variable displacement pumps type \_\_\_\_\_ axial piston  
Flow delivery \_\_\_\_\_ 2 x 38,4 l/min  
Gear pump delivery \_\_\_\_\_ 20,6 l/min  
Maximum operating pressure \_\_\_\_\_ 230 bar  
Auxiliary Flow \_\_\_\_\_ 59 l/min  
Auxiliary Pressure \_\_\_\_\_ 230 bar

### Slewing & travel speed

Slewing speed \_\_\_\_\_ 8,9 rpm  
Boom slewing angle (left/right) \_\_\_\_\_ 70° / 60°  
Travel Speed - Low (1st) \_\_\_\_\_ 2,5 km/h  
Travel Speed - High (2nd) \_\_\_\_\_ 4,5 km/h